


# UNICERAMICA QUARZO GRIGIO SCURO

|                                    |  |
|------------------------------------|--|
| <b>Origin</b>                      | Italy  |
| <b>Petrographic classification</b> | Full-body ceramic exterior tiles                   |
| <b>Appearance</b>                  | Full-body ceramic tiles for exterior applications. |
| <b>Alternative names</b>           |  |

## Usage

| <b>General</b>                      | The stone and surface finish should be selected depending on the intended use.  |                       |  |   |                      |                                     |
|-------------------------------------|---|-----------------------|--|---|----------------------|-------------------------------------|
| <b>Applications</b>                 | <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="background-color: black; color: white; padding: 2px;">Internal Applications</th> </tr> <tr> <td style="height: 80px;"></td> </tr> </table> | Internal Applications |  | <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="background-color: black; color: white; padding: 2px;">Outdoor Applications</th> </tr> <tr> <td style="padding: 5px;">           - Patio<br/>           - Swimming pool surround         </td> </tr> </table> | Outdoor Applications | - Patio<br>- Swimming pool surround |
| Internal Applications               |   |                       |  |   |                      |                                     |
|                                     |   |                       |  |   |                      |                                     |
| Outdoor Applications                |   |                       |  |   |                      |                                     |
| - Patio<br>- Swimming pool surround |   |                       |  |   |                      |                                     |
| <b>Recommendations</b>              | This material is only available in tiles  |                       |  |   |                      |                                     |

| Hardness (Mohs)   | Weight  | Water absorption   | Porosity  |
|---|---|--|---|
|  |  |  |  |
| 7   | NPD*  | < 0,1 %  | NPD*  |
|   |   | EN ISO 10545-3   |   |
| Compressive strength  | Flexural strength   | Wear resistance  | FROST RESISTANCE  |
|  |  |  |  |
| NPD*  | > 50 N/mm <sup>2</sup>  | 145 mm <sup>3</sup>  | frost resistant   |
|   | EN ISO 10545-4  | EN ISO 10545-6   | EN ISO 10545-12   |

NPD\*: geen technische gegevens beschikbaar - no technical data available - pas d' informations techniques disponibles

## Observations and recommendations

|   |
|---|
| <ul style="list-style-type: none"> <li>- Color variations and structure differences are possible as multiple prints are made per production.</li> <li>- The resistance to wear and the hardness are high, and the waterabsorption is limited. Uniceramica can be used for various applications.</li> <li>- This material can also be used for exterior applications: Uniceramica is frost and UV resistant.</li> <li>- It is a very hard, very compact material that is resistant to scratches and most staining substances. Due to the high hardness, this material is less "elastic". With sudden hard impacts, small pieces may chip off.</li> </ul> |
|---|

# UNICERAMICA QUARZO GRIGIO SCURO

## Installation

|                            |
|----------------------------|
| <b>General</b>             |
| <b>Installation system</b> |
| <b>Joint Width</b>         |
| <b> </b>                   |

General procedures of good workmanship should be followed when laying the tiles (cfr. BBRI: Belgian Building & Research Institute ref. 137 Guide for Installing - Natural Stone and ref. 213). Immediately after delivery, the material will be stored indoors or at least protected from rain, wind and frost. If slabs are damaged or broken, the supplier must be informed before installation. They will then be used, as far as possible, against walls or for certain cuts.

Before installation, the installer will examine the slabs (previously dried) with the client and / or the architect to check for any deviations from the samples. The slabs will be carefully mixed before laying, in order to obtain a harmonious distribution of colors and various shades of the material.

Important: "Installation means acceptance!", It means that AFTER the installation, no more claims will be possible, except for hidden defects.

|                        |  |
|------------------------|--|
| <b>Flooring Inside</b> | <b>Exterieur Flooring</b>  |
|                        | <p>The laying is done on a draining sub-layer. Avoid laying on concrete, because the water stagnates more easily on the surface and the terrace may freeze in winter. If you still opt for a concrete structure, apply a draining mat to the concrete before laying.</p> |

4 - 6 mm (sawn edges)

## Maintenance

|                            |
|----------------------------|
| <b>General</b>             |
| <b>First cleaning</b>      |
| <b>Regular maintenance</b> |
| <b>Protection</b>          |
| <b>Recommendations</b>     |

For more information on maintenance, see the document entitled "Care instructions" (available from us). We recommend that you follow these instructions so as not to damage the stone. The products used must be suitable for the materials. Follow the manufacturer's advice. In general, it must be stated that no moisture may be exaggerated when maintaining natural stone!

First cleaning with suitable cleaning product, eg. Lithofin KF Cement Residue Remover. This is allowed from one week after grouting the terrace.

Since the material is very compact, dirt will normally not penetrate the surface, but must be removed from the surface. Do not use cleaners with wax or greasy soaps to avoid the building of a superficial layer.

inapplicable